

U.S. ARMOR

ENFORCER XP SERIES



KEVLAR® XP™ IS A NEW WOVEN FABRIC FROM DUPONT'S FAMILY OF PERFORMANCE ARAMIDS. KEVLAR® XP™ HAS BEEN COMPLETELY REDESIGNED FOR TODAY'S MODERN THREATS. ONE OF THE KEY IMPROVEMENTS TO THIS FABRIC IS ITS ABILITY TO REDUCE THE BACK FACE DEFORMATION BY 15% OR MORE

MALE MODEL 1216M

BALLISTIC THREAT LEVEL II

PERFORMANCE DATA

NEW 9MM V50 @ 1638 FPS
NEW 357 MAG V50 @ 1682 FPS

AVERAGE BFS 9MM - 24.78MM
AVERAGE BFS 357 MAG - 28.42MM

WT. PER SQ. FT. - 13.6 OZ. - .85 LBS
THINNESS .22 INCHES

WOVEN KEVLAR XP ARAMID

BROOKWOOD FIREBALL COVER

DuPont™
KEVLAR




NIJ 0101.06 CERTIFIED

SPECIAL THREAT TESTED

WINCHESTER 9MM 127GR RANGER SXT +P+ @1261 FPS
FIOCCHI 9MM LUGER 115FR FMJ @ 1154 FPS
REM GOLDEN SABER .40 S&W 165GR BJHP @ 1145 FPS
MAG TECH .357 MAG. 158GR JSP @ 1432 FPS
SPEER .357 SIG 125GR GDHP @1371 FPS

WINCHESTER .40 S&W 165GR SXT @1049 FPS
FHN 5.7X28 SS198 40RG HP @ 1771 FPS
SPEER .45 ACP 230GR GDHP @ 878 FPS
17GR FSP FRAG - V-50 @ 1738 FPS

ALL SPECIAL THREAT TESTING IS CONDUCTED AT A NIJ APPROVED INDEPENDENT TEST LABORATORY UNLESS OTHERWISE NOTED



USARMOR.COM

U.S. Armor Corporation
800.443.9798
Sales@usarmor.com

QUALITY | SAFETY | COMFORT