

U.S. ARMOR



Model 26605 - Level IV Rifle Plate

MODEL DESIGNATION:

26605

CERTIFICATION STANDARD:

NIJ 0101.06

THREAT LEVEL:

BALLISTIC LEVEL IV (STAND ALONE)

CATEGORY:

RIFLE PLATE - SINGLE CURVE

THICKNESS:

1.00 INCHES / 25.4 MM

PLATE CONSTRUCTION:

CERAMIC & ARAMID









THREAT TESTING

THREAT	VELOCITY	
30.06 AP M2	2880 FPS.	
7.62 x 51mm - M80 BALL	2780 FPS.	
7.62 х 51мм - мМ61 АР	2780 FPS.	
5.56 х 45мм - М193	3180 FPS.	
5.56 х 45мм - М855	3180 FPS.	
5.56 х 45мм - SS109	3180 FPS.	
7.62 x 54R - LPS	2850 FPS.	
7.62 x 54R - B32 API	2850 FPS.	
7.62 х 39мм АРІ	2400 FPS.	
7.62 x 39mm Ball/Steel Core	2400 FPS.	

Width & Length	Shape	Curvature	Weight
8" x 10"	Shooter	Multi-Curve	4.80 lbs.
8" x 10"	SAPI	Multi-Curve	5.00 lbs.
8" x 10"	Full	Multi-Curve	5.10 lbs.
10" x 12"	Shooter	Multi-Curve	7.00 lbs.
10" x 12"	SAPI	Multi-Curve	7.30 lbs.
10" x 12"	Full	Multi-Curve	7.70 lbs.
8.75" x 11.75"	SAPI	Multi-Curve	6.50 lbs.
9.5" x 12.5"	SAPI	Multi-Curve	7.50 lbs.
10.25" x 13.25"	SAPI	Multi-Curve	8.50 lbs.
11" x 14"	SAPI	Multi-Curve	9.75 lbs.

