

U.S. ARMOR

ENFORCER 5000 SERIES



THE ENFORCER 5000 IS AN ADVANCED TECHNOLOGICAL DESIGN COMBINING HONEYWELL'S PROVEN GOLD FLEX®, NEW SPECTRA SHIELD® II BALLISTIC MATERIAL AND DUPONT'S KEVLAR® XP™. THE END RESULT IS A LIGHTER, MORE FLEXIBLE VEST THAT STILL SATISFIES THE STRICT PERFORMANCE REQUIREMENTS OF THE NIJ 0101.06 STANDARD.

MALE MODEL 5216M

BALLISTIC THREAT LEVEL II

PERFORMANCE DATA

NEW 9MM V50 @ 1743 FPS
NEW 357 MAG V50 @ 1668 FPS

AVERAGE BFS 9MM - 27.4MM
AVERAGE BFS 357 MAG - 31.39MM

WT. PER SQ. FT. - 13.6 OZ. - .85 LBS
THINNESS .162 INCHES

WOVEN DUPONT KEVLAR & XP, HONEYWELL
SPECTRA SHIELD & HONEYWELL GOLD SHIELD

BROOKWOOD ARCHERLITE COVERING

DuPont™
KEVLAR

Honeywell

NIJ 0101.06 CERTIFIED

SPECIAL THREAT TESTED

WINCHESTER 9MM LUGER SXT +P+ @ 1308 FPS
FIOCCHI 9MM LUGER FMJ @ 1119 FPS
WINCHESTER .40 S&W SXT @ 1165 FPS
REM GOLDEN SABER .40 S&W BJHP @ 1120 FPS
FEDERAL .40 S&W HST @ 1008 FPS
SPEER .357 SIG GDHP @ 1413 FPS
SPEER .45 ACP GDHP @ 1141 FPS

FN 5.7 X 28 MM SS197 @ 1644 FPS
2 GR. RCC PROJECTILE @ 2680 FPS
4 GR. RCC PROJECTILE @ 2241 FPS
17 GR. FSP PROJECTILE @ 1871 FPS
9MM NORMA 116 GR. FMJ @ 1260 FPS
FN 5.7X28MM SS 195 HP @ 2041 FPS

ALL SPECIAL THREAT TESTING IS CONDUCTED AT A NIJ APPROVED INDEPENDENT TEST LABORATORY UNLESS OTHERWISE NOTED



USARMOR.COM

U.S. Armor Corporation
800.443.9798
Sales@usarmor.com

QUALITY | SAFETY | COMFORT