U.S. ARMOR

ENFORCER 6000 SERIES



THE ENFORCER 6000 IS AN ADVANCED TECHNOLOGICAL DESIGN COMBINING HONEYWELL'S PROVEN ADVANCED SPECTRA SHIELD® II, AND DUPONT KEVLAR WOVEN BY SAATI. THE END RESULT IS A LIGHTER, MORE FLEXIBLE VEST THAT EXCEEDS THE STRICT PERFORMANCE REQUIREMENTS OF THE NIJ 0101.06 STANDARD.



FEMALE MODEL 6226F

BALLISTIC THREAT LEVEL II

PERFORMANCE DATA

NEW 9MM V50 @ 1700 FPS NEW 357 MAG V50 @ 1657 FPS

AVERAGE BFS 9MM - 31.62MM AVERAGE BFS 357 MAG - 35.95MM

WT. PER SQ. FT. - 11.52 OZ. - .72 LBS
THINNESS .17 INCHES

WOVEN KEVLAR ARAMID BY SAATI, HONEYWELL ADVANCED SPECTRA II

BROOKWOOD ARCHERLITE COVERING



Honeywell



SPECIAL THREAT TESTED

9MM CIVIL DEFENSE (LIBERTY) 50GR. HP @ 1999 FPS
9MM CORBON +P 115GR. JHP @ 1408 FPS
9MM WINCHESTER SXT +P+ @ 1277 FPS
.40 S&W WINCHESTER 165GR. BONDED JHP @ 1247 FPS
.40 S&W FEDERAL 165GR. HYDRA-SHOK HP @ 1099 FPS

.40 S&W SPEER 165GR. GDHP @ 1203 FPS
5.7 X 28 F/N SS195LF @ 2040 FPS
.357 SIG SPEER GDHP @ 1309 FPS
9MM FIOCCHI 115GR. FMJ @ 1159 FPS
.45 ACP 230GR. SPEER GDHP @ 926 FPS

ALL SPECIAL THREAT TESTING IS CONDUCTED AT A NIJ APPROVED INDEPENDENT TEST LABORATORY UNLESS OTHERWISE NOTED

